					11.04°P	
		I. PRODUCT IDENTIFICATION		***************************************		
	-					
				DATE PR	EPARED: January 2007	
TRADE NAME: CHEMICAL NAME:	ZETA - ZrN Zirconium Niti	ide				
		II. HAZARDOUS INGREDIENTS				
The terms "hezerdous" and "hazerdous materials" a 1200) including cited Appendices, Lists, Reference	s used within this MS s. etc., all of which he	DS should be interpreted as defined reby incorporated by reference.	by, and in accordance with O	SHA Hezard Communication	Standard (29 CFR Part 1910,	
MATERIAL OR COMPONENT		C.A.S. NO.	Wt.%	OSHA PEL (Mg/M²)	ACGIH TLV (Mg/M²)	
Zirconium, Zr Nitrogen, N ₂		7440-67-7 7727-37-9	77.7 22.3	10 N/A	5 N/A	
		III. PHYSICAL D	ATA			
BOILING POINT: SPECIFIC GRAVITY: (H ₂ O=1) VAPOR DENSITY (AIR=1) % VOLATILES BY VOLUME:		8000°F Approx. 7.0-9.0(60°f N/A N/A	SOLUBILIT	ESSURE:	5306°F N/A Insoluble E=1) N/A	
APPEARANCE:		White-Gold colored zirconium nitride is a	White-Gold colored coating about .0001" thick, odorless zirconium nitride is a chemically inert substance.			
		This extremely thin to carbide cutting to extended part life.	ilm of zirconlum nitride ols, forming tools, and	coating is applied wear parts for		
		IV. FIRE AND EXPLOS	ION DATA "	************		
FLASH POINT:		None	FIRE POINT	Ţ :	None	
***************************************	******	V. HEALTH HAZARD IN	FORMATION _			
WE OO NOT CONSIDER THE COATING IN THE MELTING, WELDING, CUTTING OR PROCESSII WHICH CAN BE INHALED, SWALLOWED, OR O PARTICLES OF ZIRCONIUM NITRIDE TOGETHI MSDS SHEETS FOR SUBSTRATE MATERIAL FI	OME IN CONTACT W	THE SKIN OR EYES. THE DU	STOR FUMES WHICH CAN	DUCE POTENTIALLY HAZAR BE INHALED, WILL CONSIS	DOUS DUST OR FUMES	
PRIMARY ROUTES OF ENTRY:	Inh	nalation EMERGENCY FIR		con	D: Remove to fresh air, if continue, consult physician.	
	Ey	è Contact		to r	sh well with water emove particulate. t medical attention.	
	Sk	in Contact		Wa	ish off excess dust, ish out area with ap and water.	
	ing	estion			ek medical help if ge quantities of material	

EFFECT OF EXPOSURE: No toxic effects would be expected from exposure to the solid form of zirconium nitride coated toxis. Prolonged, repeated exposure to fumes or dust generated during heating, cutting, brazing or welding may or may not cause adverse heath effects associated with the listed constituents in axcess of OSHA permissible exposure limits established in 29 CFR Subpart Z. (See Section II)

have been ingested.

EXPOSURE LIMITS: Section II lists specific ingredients and permissible exposure limits Determine actual exposure by industrial hygiene monitoring POSSIBLE SIGNS AND SYMPTOMS OF EXPOSURE TO DUST, WELDING, FUME AND GASES: SHORT TERM EXPOSURE: Metallic taste; neusea, tightness of chest; fever; irritation of eyes, nose throat and skin; loss of consciousness / death due to welding gases or lack of oxygen. There are no adverse effects for zirconium nitride coated products in there solid form. Adverse effects may or may not result from long-term (chronic) exposure to dust, furne, gases, etc. that occur by way of subsequent operations on the zirconium nitride coated product. It is believed there are nor reliable scientific studies which show that workers exposed to operations upon zirconium nitride coated products suffer increased incidence of lung cancer or other disease because of exposure to zirconium nitride. Some studies would associate elements from various substrate materials (material the coated object is made of) with the potential for neurologic, pulmonary, skin or other disease. Chromium, cobalt and nickel in various chemical compounds have been identified as suspect human carinogens by the I.A.R.C., N.T.P. annual report. Users of zirconium nitride coated products should check MSDS sheets of substrate material for possible health hazard effects form material of coated object. VI. REACTIVITY DATA STABILITY: Chemically Stable IMPCOMPATIBILITY: Reacts with strong acids **HAZARDOUS DECOMPOSITION PRODUCTS: Metallic Oxides** VII. SPILL OR LEAK PROCEDURES STEPS TO BE TAKEN IN CASE OF RELEASE OR SPILL: N/A WASTE DISPOSAL METHOD: Solids -Sales as scrap for reuse Dust, etc. -Follow federal, state and local regulations regarding disposal. ****** VIII. SPECIAL PROTECTION INFORMATION *******************

VENTILATION REQUIREMENTS:

General - Recommended (to keep airborne concentration of dust and fumes below ACGIH TLV's

Local - As required

PERSONAL PROTECTIVE EQUIPMENT:

Respiratory:

If fumes, missing or dust condition occurs and TLV as indicated in Section II is exceeded, provide

NIOSH approved respirators.

Eye Protection:

Recommended approved safety glasses of goggles when working with dusty material.

Gloves:

As required

Other Clothing or Equipment:

As required

IX. SPECIAL PRECAUTIONS

USE GOOD HOUSE KEEPING PRACTICES TO PREVENT ACCUMULATIONS OF DUST AND TO KEEP AIRBORNE DUST CONCENTRATIONS AT A MINIMUM.

THIS MATERIAL IS POTENTIALLY CONTAMINATED WITH COATING SUCH AS OILS FOR PRESERVATIVES AND OTHER CONTAMINANTS, IF THE MATERIAL IS CONTAMINATED, SPECIAL PRECAUTIONS (SUCH AS PROCESS CONTROL, AND PERSONAL PROTECTIVE EQUIPMENT APPRORIATE TO THE NATURE OF THE SUSSPECTED CONTAMINANTS SHOULD BE TAKEN TO AVOID RESULTING EXPOSURES WHEN HANDLING, CUTTING (THERMAL OR MECHANICAL) AND/OR HEATING OR MELTING.

While the information set forth in this material safety data sheet is believed to be accurate, as of the effective data, Metallurgical Processing, Inc. make no representations regarding the accuracy or completeness of the information and assumes no Kability for any loss, damage, or injury of any kind which may result from or arise out of the use or reliance on the information by any person.

N/A = NOT APPLICABLE